



Packaging machine with flow pack system, which allows you to flop the products in such a way as to guarantee a longer shelf life of the product itself.
 The wrap 400 allows the packaging of different products, with different formats.
 It is possible to choose between different types of packaging material.
 The machine is equipped as standard with all the optionals on the market, in order to attract a very high range of customers, making its use very simple, thanks to its completeness, even for those approaching a wrapping machine for the first time.

Mechanical characteristics

Overall dimensions	[mm] (LxWxH) 2500x720x1800
Empty weight	[kg] 450
Material in contact with food	inox AISI 304 L
N° swivelling wheels	4

Cooling system characteristics

Cooling group	[Fr/h] 900
Refrigerant gas	R134A
Refrigerant gas quantity	[g] 100
Coolant	[l] 1,5
70% water, 30% phosphate-free glycol	

Electrical characteristics

Total installed power	[kW] 2
Supply voltage	[VAC] 220
Number of phases	1
Frequency	[Hz] 50 / 60
Auxiliary voltage	[Vdc] +24
Enclosure degree of protection	IP65
Connection type: industrial plug	16A - 3 poles

Characteristics pneumatic system

Minimum working pressure	[bar] 6
Minimum flow rate	[l/min] 100
Air characteristics	filtered, dry and de-oiled

